## Custom Installation CWM652



## See nothing, hear everything

The CWM652 features a 130mm (5in) blue Aramid Fibre bass/midrange driver housed in a die-cast chassis which provides the extra rigidity to provide a cleaner, faster bass. Its aluminium tweeter incorporates a Nautilus<sup>™</sup> tube to absorb unwanted sonic radiation. The CWM652 also utilises a three-position high frequency switch to fine tune the sound. The incredibly easy to install frame includes QuickDogs<sup>™</sup> and plug-and-play functionality.

## **Technical Specifications**

Description	2-way in-wall system
Drive units	1x ø25mm (1in) Nautilus <sup>™</sup> tube loaded aluminium dome tweeter 1x ø130mm (5in) blue Aramid Fibre cone bass/midrange
Frequency Range (-6dB)	54Hz – 50kHz
Maximum Amp Power	25 – 100w
Sensitivity SPL (2.83V, 1m)	86dB
Impedance Nominal (min)	8Ω (4.5Ω)
Frame height	264mm (10.9in)
Frame width	191mm (7.5in)
Cut-out height	228mm (9in)
Cut-out width	153mm (6in)
Depth behind surface	95mm (3.7in)
Protrusion	4mm (0.2in)
Pre-mount Kit	PMK W5
Back Box	BB 6W



## Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE

