
# Bowers & Wilkins

# Custom Installation CWM8.5 D





## See nothing, hear everything

CWM8.5 D is a two-way in-wall loudspeaker. It offers exceptionally high performance from a compact loudspeaker.

It features a decoupled Diamond dome tweeter and a single 7inch bass/mid Continuum driver with anti-resonance plug.

For optimum discretion when installed, the Continuum cone is given a dark finish.

#### **Technical Specifications**

**Description** 2-way in-wall loudspeaker

**Technical features** Diamond Dome, Nautilus™

tube-loaded tweeter Anti-resonance plug

Flowport™

**Drive units** 1x ø25mm (1in) Diamond Dome,

Nautilus™ tube-loaded tweeter

1x Ø180mm (7in) Continuum cone bass/midrange driver with anti-resonance plug

Frequency range (-6dB) 35Hz - 35kHz

Recommended

**Amplifier Power** 120W

Sensitivity 89dB

Nominal Impedance  $8\Omega$ 

Frame height 411mm (16.2in)

Frame width 247mm (9.7in)

**Cut-out height** 395mm (15.5in)

Cut-out width 231mm (9.1in)

**Protrusion** 8mm (0.3in)

Net weight 3.5kg

Back Box BB CWM8.5

### Bowers & Wilkins

www.bowers-wilkins.com